

SYMBOL(S)	ITEM NO.	USED TO MOUNT	QTY	USED ON		Ø
				MODEL	DATE	
				MFP-1	10/13/64	A3564
DS7002	1			A3563		
DS7001	2					
XF7001	3	HA102	4			
DS7003	4					
R7017						
XF7002						
DS7004						
R7018						
XF7003						
DS7005						
R7019						
F7003	5					
F7002	6					
F7001	7					
F7002	8					
	12	HA102	4			
	13	NP102	4			
XDS7002	14					
XDS7001	15					

LIGHT, INDICATOR, AMBER
 LIGHT, INDICATOR, RED
 SCREW, TAP., THREAD CUTTING
 SCREW, MACHINE
 PLATE, IDENT, COMMERCIAL
 PANEL, FRONT
 HANDLE, BOW
 FUSE, CARTRIDGE, 6-1/4 A, 115V ONLY
 FUSE, CARTRIDGE, 1/2 A
 FUSE, CARTRIDGE, 3A, 230V ONLY
 FUSE, CARTRIDGE, 1/10 A
 FUSEHOLDER, INDICATOR
 FERRULE, HANDLE
 LAMP, GLOW
 LAMP, INCANDESCENT

TS154-3
 TS153-1
 SFB0256SN3
 SCFP1032BN8
 NP102-64
 LD1448/MS3694
 HA102-13BN
 FU102-6.25
 FU102-.5
 FU102-3
 FU102-.1
 FH104-2
 CU139-2B
 B1111-1
 B1110-8

REQ. PER UNIT	ITEM	PART NO.	DESCRIPTION	SYMBOL
1	15	TS154-3	LIGHT, INDICATOR, AMBER	
1	14	TS153-1	LIGHT, INDICATOR, RED	
4	13	SFB0256SN3	SCREW, TAP., THREAD CUTTING	
4	12	SCFP1032BN8	SCREW, MACHINE	
1	11	NP102-64	PLATE, IDENT, COMMERCIAL	
1	10	LD1448/MS3694	PANEL, FRONT	
2	9	HA102-13BN	HANDLE, BOW	
1	8	FU102-6.25	FUSE, CARTRIDGE, 6-1/4 A, 115V ONLY	
1	7	FU102-.5	FUSE, CARTRIDGE, 1/2 A	
1	6	FU102-3	FUSE, CARTRIDGE, 3A, 230V ONLY	
1	5	FU102-.1	FUSE, CARTRIDGE, 1/10 A	
3	4	FH104-2	FUSEHOLDER, INDICATOR	
4	3	CU139-2B	FERRULE, HANDLE	
1	2	B1111-1	LAMP, GLOW	
1	1	B1110-8	LAMP, INCANDESCENT	
A ALT.				
THE TECHNICAL MATERIEL CORP.				
MAMARONECK, NEW YORK				
PANEL ASSEMBLY, FRONT				
REQ. PER UNIT	ITEM	PART NO.	DESCRIPTION	SYMBOL
			ENG COORD	
			DRAWN	
			CHECKED	
			10-23-64	
			L. J. Gabel	
			FINAL APPROVAL	
			A3564	
			ELEC. DES. APP.	
			MECH. DES. APP.	
			FINISH & SPEC. NO.	
			SCALE	
			DATE	
			10-29-64	
			CH. NO.	
			Ø	
			DRAFTS	
			J.L.	
			CHECKER	
			ENG. APP.	
			DESCRIPTION	
			ORIGINAL RELEASE FOR PRODUCTION	
			UNLESS OTHERWISE SPECIFIED	
			DIMENSIONS ARE IN INCHES AND INCLUDE	
			CHEMICALLY APPLIED OR PLATED FINISHES	
			FRACTIONS	
			± 1/64	
			ANGLES,	
			± 0° 30'	
			TOLERANCES	
			.X ± .05	
			.XX ± .01	
			.XXX ± .005	