

SYMBOL(S)	ITEM NO.	USED TO MOUNT	QTY	USED ON	
				MODEL	DATE
				LFC-A-1	4/15/65
				A3892	A3895

C104	1			
	2	CE112-2N	1	
	3	RW107-18	2	
	5	CU145A1	3	
	6	RW107-18	2	
	6	CU145A1	3	
	7	RW107-18	2	
K101				
R101, 107				
	9	CU145A1	3	
	10	RW107-18	2	
	11	CU145A1	2	
XK101	12			
CR101	13			
	14	RW107-18	4	
CR104	15			
CR102	16			
C.A.103	17			

REQ. PER UNIT	MODEL	ASSY. NO.	DATE
1	LFC-A-1	A3892	4/15/65

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
1	IN2978RB	SCOND DEV, DIO	
1	IN2976B	SCOND DEV, DIO	
1	IN2484	SCOND DEV, DIO	
4	WA102-4	WASH., NM	
1	VR101-24S51	SCOND DEV, DIO-ZNR	
1	TS171-1	SOC, RELAY-W/RET.	
2	TE149-144	TERM., LUG-NO. 6	
2	SCBP0632BN22	SCR, MAGH	
3	SCBP0632BN5	SCR, MAGH	
2	RW107-18	RES, FXD, WW-5W-50 OHMS	
1	RL156-1	REL, ARM. -DPDT	
5	NTH0632BN8	NUT, PLN, HEX	
5	LWE06MRN	WASH., LK, EXT	
1	LD1575/MS3933	PL, MTG, CAP. /REL	
2	FW06HBN	WASH., FLAT	
1	CU145A1	RET., CAP.	
1	CE112-2N	CAP., FXD, ELECT.	
		POSE	
		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
		CAPACITOR/RELAY ASSEMBLY	
		STOCK SIZE	
		MATERIAL	
		TYPE & TEMPER	HEAT TREAT. SPEC.
		FINISH & SPEC. NO.	

4-30-65

ORIGINAL RELEASE FOR PRODUCTION

DATE: 4-30-65

SCALE: 1/64

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

TOLERANCES: ± 1/64 ANGLES ± 0° 30'

DECIMALS: .X ± .05, .XX ± .01, .XXX ± .005

FRACCTIONS: ± 1/64 ANGLES ± 0° 30'

SYMBOL: Ø

DESCRIPTION: ORIGINAL RELEASE FOR PRODUCTION

DATE: 4-30-65

SCALE: 1/64

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

TOLERANCES: ± 1/64 ANGLES ± 0° 30'

DECIMALS: .X ± .05, .XX ± .01, .XXX ± .005

FRACCTIONS: ± 1/64 ANGLES ± 0° 30'

SYMBOL: Ø

DESCRIPTION: ORIGINAL RELEASE FOR PRODUCTION

DATE: 4-30-65

SCALE: 1/64

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

TOLERANCES: ± 1/64 ANGLES ± 0° 30'

DECIMALS: .X ± .05, .XX ± .01, .XXX ± .005

FRACCTIONS: ± 1/64 ANGLES ± 0° 30'