


CA1226

SYMBOL - DENOTES

- = ITEM NO'S
- = LUGS
- = WIRE MARKERS




THIS SYMBOL DENOTES END OF INSULATION AND NAIL DRIVING POINT. WIRE MUST BE STRIPPED 3/4" BEYOND THIS POINT AND TINNED 1/2" UNLESS OTHERWISE SPECIFIED.

UNLESS OTHERWISE SPECIFIED
WIRES SHOULD BE PLACED IN CABLE IN NUMERICAL SEQUENCE AS THEY APPEAR IN ITEM COLUMN BY CATEGORY.

1. ALL R.F. CABLES
2. ALL SHIELDED CABLES
3. ALL OTHERS

SPACE LACING APPROXIMATELY 3/4" APART.



NOTES

1	GPT-10KLF	
Q'TY./UNIT	MODEL USED ON	ASS'Y. NO.
SCALE 1:1	CODE A	
THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.		

REVISIONS						
SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD	APPD
Ø	ORIGINAL RELEASE FOR PRODUCTION	2-16-66	-M	Jc		

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
X	11	BS100	SOLDER, TIN, ALLOY	
X	10	CD101-1-MW	CORD, NYLON, LACING	BLACK
6	9	LA101	BAND, MARKER, CBL	
6	8	TE120-2	TERM, LUG, SPADE	
	7	PX100-1-315	INS, SLVG, ELECT.	BLACK
	6	MWC 18(16)U4	WIRE, ELECT, INS.	YELLOW
	5	MWC 20(7)U94		WH/YEL
	4	U91		WH/BRN
	3	U1		BROWN
	2	U9		WHITE
	1	MWC 20(7)U6	WIRE, ELECT, INS.	BLUE

F. BUDETTI		LIST OF MATERIAL			
MATERIAL		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK			
FINISH		TITLE CABLE ASSEMBLY (AR-178) P.A. BIAS			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		DRAWN <i>[Signature]</i>	DATE 12-6-65	FINAL APPROVAL <i>[Signature]</i>	DATE 2/16/66
DECIMALS .X ± .05 .XX ± .01 .XXX ± .005		TOLERANCES		ELECT. DES. <i>[Signature]</i>	
FRACTIONS ± 1/64 ANGLES ± 0° 30'		MECH. DES. <i>[Signature]</i>		DATE 2-15-66	
		DATE 2/11		SHEET Ø	
				REV. LTR.	