



OPPOSITE SIDE SAME

1 MOUNT IN "B" HOLES AFTER FINISHING

MARK TMC P/N 1/8 HIGH GOTHIC W/LATEST REV LETTER (THIS SIDE ONLY)

NOTE: MARK PARTING PER TMC SPEC S127

MS 5069

REVISIONS		DATE	E.M.N. NO.	DRAFT	CHKD	APPD
X	EXPERIMENTAL RELEASE	9/2/66	X.	CED		
Ø	ORIGINAL RELEASE FOR PRODUCTION	3-20-67		L.A.K.		

HOLE CHART			
SYM	DESCRIPTION	REQ'D	
A	11/64 DIA	6	
B	.191-.194 DIA	4	
C	1" DIA	3	

- UNLESS OTHERWISE SPECIFIED:
1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS
  2. ALL ANGULAR BENDS 90 DEGREES
  3. REMOVE ALL BURRS AND SHARP EDGES
  4. MOUNT INSERTS AFTER FINISHING

REF: LD2157 (NOTE (2) BRACKETS REQ/UNIT, ONLY (1) TO BE LETTERED.)

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
4	1	NT-129-632-4	NUT, ROUND, SWAGE TYPE	

**LIST OF MATERIAL**

**MATERIAL**  
 .063 ALUMINUM  
 5052-H32

**FINISH**  
 S404 YEL IRIDITE

**TITLE**  
 BRACKET, MOUNTING, RESISTOR

**THE TECHNICAL MATERIEL CORP.**  
 MAMARONECK, NEW YORK

QTY./UNIT	2	MODEL USED ON	PSP 350C	ASSY. NO.	
SCALE	1:2	CODE			

NOTES

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.