



REQ. PER UNIT	USED ON			MS6021	Ø
	MODEL	ASS'Y. NO.	DATE		
1	RFA-1B		10.20.66		

HOLE	DESCRIPTION	REQ
A	.161-.164 DIA	1
B	1/8 DIA	1

UNLESS OTHERWISE SPECIFIED:

1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS
2. ALL ANGULAR BENDS 90 DEGREES
3. REMOVE ALL BURRS AND SHARP EDGES
4. MOUNT INSERTS AFTER FINISHING

MOUNT IN "A" HOLE AS SHOWN

									1	1	NT129-440-4	NUT, PLAIN, SPLINE, TYPE	A
									REQ. ITEM		PART NO.	DESCRIPTION	SYMBOL
											.064	THE TECHNICAL MATERIEL CORP.	
											STOCK SIZE	MAMARONECK, NEW YORK	
											ALUMINUM	BRACKET, R.F. COVER	
											MATERIAL		
											5052-H32	WHO	AD 10/21/66
											TYPE & TEMPER	CHECKED	FINAL APPROVAL
											S404 YEL IRIDITE		
											FINISH & SPEC. NO.	ELEC. DES. APP.	MECH. DES. APP.
													MS6021
													Ø

Ø ORIGINAL RELEASE 10/21/66

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

DECIMALS .X ± .05 .XX ± .01 .XXX ± .005 FRACTIONS ± 1/64 ANGLES ± 0° 30'

SCALE 2/1