



LENGTH ALLOWS 3/8 EACH END FOR STRIPPING

Fiberglass-
Fiberglass-

X	5	BS-100	SOLDER, SOFT	
3 1/4	4	PX-342-1-294	SLEEVING	
10	3	MWC12(19)B9	CABLE FROM INSULATED V606 PIN F T603 PIN 7	WHITE
6 3/4	2	MWC12(19)B90	CABLE FROM INSULATED V606 PIN F T603 PIN 5	WH/BLACK
4	1	TE-141-3	LUG	
REQ. ITEM	PART NO.		DESCRIPTION	SYMBOL
CRO			THE TECHNICAL MATERIEL CORP.	
STOCK SIZE			MAMARONECK, NEW YORK	
CRO			CABLE ASS'Y, FILAMENT,	
MATERIAL			JUMPER, HV RECT, RTP-2	
CRO	CRO	10-30-58	DRAWN	CHECKED
TYPE & TEMPER		HEAT TREAT. SPEC.	FINAL APPROVAL	
CRO			CA-405 A	
FINISH & SPEC. NO.		ELEC. DES. APP.	MECH. DES. APP.	

ISSUE	ITEM	CHANGED FROM	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
A	2	ITEM(2) WAS MWC12(19)J90	2-25-63	8318			
	1	ITEM(3) WAS MWC12(19)J9					
TOLERANCES			SCALE: CRO				
DEC. DIM. ±			MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION.				
FRAC. DIM. ±			REMOVE ALL BURRS AND SHARP EDGES				
ANGULAR DIM. ±							

1	RTP-2			10-30-58
REQ. PER UNIT	MODEL	PROJECT NO.	ASS'Y. NO.	DATE
USED ON				