



REVISIONS					
SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD APPD
X	EXPER. RELEASE	1-25-65	X		JM
Ø	ORIGINAL RELEASE FOR PRODUCTION	2-16-65	Ø		JOB

HOLE LEGEND

HOLE	DESCRIPTION	REQ'D
"A"	.221-.224 DIA	2
"B"	1/64 DIA	9
"C"	13/32 DIA	1

METAL STAMP TMC P/N  
W/LATEST REVISION LETTER

UNLESS OTHERWISE SPECIFIED:

1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS
2. ALL ANGULAR BENDS 90 DEGREES
3. REMOVE ALL BURRS AND SHARP EDGES
4. MOUNT INSERTS AFTER FINISHING

2	1	NT129-832-4	NUT, PLAIN, SPLINE	A
REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL

EATON		LIST OF MATERIAL		SK-3071-MS-8
MATERIAL		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK		
.081 THK ALUMINUM 5052-H32		TITLE CHASSIS, ELECTRICAL-SIDE (+180V POWER SUPPLY)		
FINISH		DRAWN		
YELLOW IRIDITE S902		DATE		

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		DATE		DATE	
DECIMALS		FRACTIONS		DATE	
.X ± .05		± 1/64		2/8/65	
.XX ± .01		ANGLES		DATE	
.XXX ± .005		± 0° 30'		2/8/65	
TOLERANCES		ELECT. DES.		DATE	
		W. JORDAN		2/8/65	
		MECH. DES.		DATE	
				2/8/65	
		SHEET		REV. LTR.	

1	RTIA-1	A 4058
Q'TY./UNIT	MODEL USED ON	ASS'Y. NO.
SCALE	CODE	
	A	

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

NOTES