

OTTAWA, ONTARIO
 TMC(Canada)LIMITED

BILL OF MATERIAL		MODEL LF/MF Beacon				PROJ. NO.				LIST NO. ML-10024	
		ISSUE								SHEET 1 OF 1 SHEETS	
PART NO.	QUAN. PER ONE EQUIP.	DESCRIPTION						REMARKS			
								MFG. NO.			
		LF/MF Beacon c/o Dummy Load									
NP-10001-6	.45	1	Name Plate, 3" x 2"						Markrite		
MS-10102	.02	1	Stud, 1 1/8" x 1/2", 1/8" alum., 65ST								
MS-10107	.08	4	Strip Screen Vent Frame, 4" x 1/2", .064 alum. 57S-1/4"H								
MS-10103	.04	2	Bracket, 6" x 1 17/32", .064 alum., 57S-1/4"H								
SN-10001	.50	2	Screen, Vent, 10 1/4" x 4 3/4", 14 mesh stainless steel								
MS-10106	.16	4	Strip, Screen Vent Frame, 10 1/2" x 1/2", .064 alum., 57S-1/4"H								
PP-10054	.50	2	Mounting Strip, 11" x 2" x 1/4", Phenolic XXX								
MS-10105	.40	2	Side Panels, 9 7/16" x 9 3/16", .064 alum., 57S-1/4"H								
MS-10098	3.85	1	Panel, front, MS-157-6, 19" x 10 15/32"								
MS-10100	.30	1	Bottom cover, 8 9/16" x 14 1/8", .064 alum., 57S-1/4"H								
MS-10099	.40	1	Cover, top, 14 1/8" x 15 1/8", .064 alum., 57S-1/4"H								
DA-10001	34.20	1	Dummy Load Assembly (3) 225 ohm, 500W resistor mat in parallel c/w mtg. frame.						Ohmweve Co.		
	.15	14"	Braid 3/16" copper								
NT-108-1	.05	13	Nut Speed, 0632								
SCBSO440BC7	.05	8	Screw, machine, 4-40 3/16								
SCBSO632BC5	.15	48	Screw, machine								
NTHO632BC8	.15	36	Nut, hexagonal								
LWSO6MRC	.10	36	Lockwasher								
LWSO4MRC	.03	8	Lockwasher								
SO-239	.41	1	Connector, receptacle						Amphenol 83-IR		
PL-259	.42	1	Connector, plug						Amphenol 83-1SP		
PX-100-1.234	.03	14"	Insulation sleeving black								
TE-104-1	.01	4	Terminal, locking						Shakeproof 2104-04-00		
TE-104-2	.01	2	Terminal, locking						Shakeproof 2101-06-00		
NTHO440BC6	.05	8	Nut, hexagonal, 4-40, 3/16"								
W2-100-6	.01	2 1/2"	Bus bar wire no. 20								
		42.51									

↑ APPLICABLE SPECIFICATIONS. LAST PAGE ↓

CHECKED

APPROVED

number changed to ML-10024

TMC(Canada)LIMITED
OTTAWA, ONTARIO

BILL OF MATERIAL		MODEL LF/MF Beacon c/o	PROJ. NO.	LIST NO. BM-10015
		ISSUE		SHEET 1 OF 1 SHEETS
PART NO.	QUAN. PER ONE EQUIP.	DESCRIPTION		REMARKS
		LF/MF Beacon c/o Dummy Load		
NP-10001-6	1	Name Plate, 3" x 2"		<i>superseded</i>
MS-10104	4	Spacer, 5" x 1 7/32", .064 alum., 57S-1/4"H		
MS-10102	1	Stud, 1 1/8" x 1/2", 1/8" alum., 65ST		
MS-10107	4	Strip Screen Vent Frame, 4" x 1/2", .064 alum., 57S-1/4"H		
MS-10103	2	Bracket, 6" x 1 17/32", .064 alum., 57S-1/4"H		
MS-10101	4	Bracket, 6 3/4" x 3 1/2", .064 alum., 57S-1/4"H		
SN-10001	2	Screen, Vent, 10 1/4" x 4 3/4", 14 mesh stainless steel		
MS-10106	4	Strip, Screen Vent Frame, 10 1/2" x 1/2", .064 alum., 57S-1/4"H		
PP-10054	2	Mounting Strip, 11" x 2" x 1/4", Phenolic XXX		
MS-10105	2	Side Panels, 9 7/16" x 9 3/16", .064 alum., 57S-1/4"H		
MS-10098	1	Panel, front, MS157-6, 11 1/2" x 10 15/32		
MS-10100	1	Bottom cover, 8 9/16" x 14 1/8", .064 alum., 57S-1/4"H		
MS-10099	1	Cover Top, 14 1/8" x 15 1/8", .064 alum., 57S-1/4"H		
DA-10001	1	Dummy Load Assembly (3) 225 ohm 500W resistor mat in parallel c/w mtg. frame.		
	14"	Braid 3/16", copper		
NT-108-1	13	Nut Speed, 0632		
SCBS0440BC7	8	Screw, machine 440 7/16" NTH0440BC6 -4		
SCBS0632BC5	29 168	Screw, machine <i>ada</i>		
NTH0632BC8	16 36	Nut, hexagonal		
LWS06MRS	16 36	Lockwasher		
LWS04MRS	8	Lockwasher		
GU-104-5	2	Clamp, cable		
SO-239	1	Connector, Receptical		
PL-259	1	Connector, plug		
PX-100-1-234	14	INSULATION SLEEVING, <i>black</i>		
TE-104-1	4	TERMINAL LOCKING		
TE-104-2	2	" "		

↑ APPLICABLE SPECIFICATIONS, LAST PAGE ↓

CHECKED

APPROVED